

# Titan 3-Phase Single

Type	Downlight
Mounting	3-Phase rail (Eutrac adapter)
Material	Aluminium
Adjustable	Yes (90°/359°)
El. class / IP	Class I / IP20
Warranty: see p.348	

<b>Bridgelux Vero 10 LED (350mA)</b>	
CCT	2700K / 3000K / 4000K
CRI	Ra90 (Ra80 on request)
SDCM	3
Luminous Flux LED	2700K - Ra90: 1100lm (124lm/W) 3000K - Ra90: 1156lm (130lm/W) 4000K - Ra90: 1172lm (132lm/W)
Luminous Flux System	2700K - Ra90: 937lm (92lm/W) 3000K - Ra90: 984lm (96lm/W) 4000K - Ra90: 998lm (98lm/W)
Beam angle	28° / 40°
LED Power	8.9W / 350mA (excl. driver)
System Power	10.2W / 350mA (incl. driver)



Weight: 865g



**Mounting on horizontal tracks only!**

**Driver:**  
- integrated in luminaire  
- included in article number and price

**Data sheets and wiring guide: see website**

**On Request**

LED with CRI Ra97  
Class A LED



## Titan 3-Phase

Cone

**PRICES INCL. BUILT-IN DRIVER**

### Non Dimmable (universal adapter)

2700K - Ra90 - 10.2W - 937lm	1226.AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1226.AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1226.AA.24.940.XX

### DALI Dimmable (only for Eutrac DALI tracks)

2700K - Ra90 - 10.2W - 937lm	1226.AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1226.AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1226.AA.26.940.XX



## Titan 3-Phase

Organic

**PRICES INCL. BUILT-IN DRIVER**

### Non Dimmable (universal adapter)

2700K - Ra90 - 10.2W - 937lm	1227.AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1227.AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1227.AA.24.940.XX

### DALI Dimmable (only for Eutrac DALI tracks)

2700K - Ra90 - 10.2W - 937lm	1227.AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1227.AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1227.AA.26.940.XX



## Titan 3-Phase

Anti-Glare

**PRICES INCL. BUILT-IN DRIVER**

### Non Dimmable (universal adapter)

2700K - Ra90 - 10.2W - 937lm	1228.AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1228.AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1228.AA.24.940.XX

### DALI Dimmable (only for Eutrac DALI tracks)

2700K - Ra90 - 10.2W - 937lm	1228.AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1228.AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1228.AA.26.940.XX

28° Reflector: 0000.28.00.000.00  
40° Reflector: 0000.40.00.000.00

Available colors: 0000.00.00.000.XX  
Other RAL colors on request



01 White Matt Text. Standard



18 Grey Matt Text. Standard



03 Black Matt Text. Standard



25 Smoked Brown Text. Standard



11 Black + Gold Matt Text. Standard