

Titan Mix

Square

Type	Downlight
Mounting	Recessed
Material	Aluminium
Adjustable	Yes (40°/359°)
El. class / IP	Class III / IP20
El. class driver	Class II
Warranty: see p.348	



Bridgelux Vero 10 LED (350mA)

CCT	2700K / 3000K / 4000K
CRI	Ra90 (Ra80 on request)
SDCM	3
Luminous Flux LED	2700K - Ra90: 1100lm (124lm/W) 3000K - Ra90: 1156lm (130lm/W) 4000K - Ra90: 1172lm (132lm/W)
Luminous Flux System	2700K - Ra90: 937lm (92lm/W) 3000K - Ra90: 984lm (96lm/W) 4000K - Ra90: 998lm (98lm/W)
Beam angle	28° / 40°
LED Power	8.9W / 350mA (excl. driver)
System Power	10.2W / 350mA (incl. driver)
Forward voltage	23V (min.) - 25.5V (typ.) - 28V (max.)


Bridgelux Dim-to-warm LED (more info see p.330)

CCT	Dim-to-warm 1800-3000K
CRI	Ra90
Luminous Flux LED	LED: 860lm - System: 732lm
LED Power	8.2W / 250mA (excl. driver)
System Power	9.4W / 250mA (incl. driver)

DIM TO WARM



Weight: 330g
(excl. driver)



Living Tomorrow Brussels - Bellén Architects

Driver:

- Included in article number and included in price
- External/Remote installation


Data sheets and wiring guide: see website
Driver information: see p.334-335

On Request

LED with CRI Ra97
Class A LED

Air circulation notice:

Do not topload with insulation materials





Titan Mix Square

Cone

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1006.AA.24.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1006.AA.24.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1006.AA.24.940.XX-Y

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1006.AA.25.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1006.AA.25.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1006.AA.25.940.XX-Y

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1006.AA.26.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1006.AA.26.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1006.AA.26.940.XX-Y

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1006.AA.27.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1006.AA.27.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1006.AA.27.940.XX-Y

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1006.AA.26.dtw.XX-Y
-------------------------------	---------------------

Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1006.AA.27.dtw.XX-Y
--------------------------------	---------------------



Titan Mix Square

Organic

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1004.AA.24.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1004.AA.24.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1004.AA.24.940.XX-Y

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1004.AA.25.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1004.AA.25.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1004.AA.25.940.XX-Y

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1004.AA.26.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1004.AA.26.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1004.AA.26.940.XX-Y

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1004.AA.27.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1004.AA.27.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1004.AA.27.940.XX-Y

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1004.AA.26.dtw.XX-Y
-------------------------------	---------------------


Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1004.AA.27.dtw.XX-Y
--------------------------------	---------------------


Trapezium springs: 0000.00.00.000.00-**T**
Boobytrap springs: 0000.00.00.000.00-**B**



TRAPEZIUM SPRINGS



BOOBYTRAP SPRINGS



Titan Mix Square

Anti-glare

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1005.AA.24.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1005.AA.24.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1005.AA.24.940.XX-Y

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1005.AA.25.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1005.AA.25.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1005.AA.25.940.XX-Y

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1005.AA.26.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1005.AA.26.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1005.AA.26.940.XX-Y

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1005.AA.27.927.XX-Y
3000K - Ra90 - 10.2W - 984lm	1005.AA.27.930.XX-Y
4000K - Ra90 - 10.2W - 998lm	1005.AA.27.940.XX-Y

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1005.AA.26.dtw.XX-Y
-------------------------------	---------------------

Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1005.AA.27.dtw.XX-Y
--------------------------------	---------------------

28° Reflector: 0000.28.00.000.00-0
40° Reflector: 0000.40.00.000.00-0

Available colors: 0000.00.00.000.XX-0
Other RAL colors on request



01 White Matt Text. Standard



18 Grey Matt Text. Standard



03 Black Matt Text. Standard



25 Smoked Brown Text. Standard



22 White + Chrome (Organic only)



21 Black + Chrome (Organic only)



11 Black + Gold Matt



16 Gold Matt