

Palladium T2

Technical Datasheet

DOXIS
LIGHTING FACTORY



General specs

| | |
|----------|-------------------|
| Type | Suspended |
| Material | Polyethylene |
| Lamp | LED Module/ Titan |
| Dimmable | Touchdim / DALI |

IP20 850°C



Features:
Suspended UFO-shaped Lounge luminaire.
Power supplies / Control gear included.

| Palladium T2 | | Lightsource | LED Output* | Power** | LED Efficacy* | Power supply | CCT | CRI | Life L70B50 |
|--|----------------|-------------------------------------|---------------------|------------------|---------------|----------------------------------|------|-----|-------------|
| Art. nr. | Im | W | lm/W | K | Ra | Hrs | | | |
| LED 6480lm + 3x | 376.LED.830 | Philips LEDStrip (incl.) + 3x Titan | 6480lm + (3x) 867lm | 46.8 + (3x) 8.9W | 124 | Driver non dim. (incl.) | 3000 | 80 | 50000 |
| | 376.LED.830-TD | Philips LEDStrip (incl.) + 3x Titan | 6480lm + (3x) 867lm | 46.8 + (3x) 8.9W | 124 | Driver touch dim. / DALI (incl.) | 3000 | 80 | 50000 |
| | 376.LED.840 | Philips LEDStrip (incl.) + 3x Titan | 6750lm + (3x) 867lm | 46.8 + (3x) 8.9W | 124 | Driver non dim. (incl.) | 4000 | 80 | 50000 |
| | 376.LED.840-TD | Philips LEDStrip (incl.) + 3x Titan | 6750lm + (3x) 867lm | 46.8 + (3x) 8.9W | 124 | Driver touch dim. / DALI (incl.) | 4000 | 80 | 50000 |

Options

Suspension + white power cable 4000mm

White 4000mm - 3x0.75mm² 102.33.01-4
White 4000mm - 5x0.75mm² 102.35.01-4
White 4000mm - 7x0.75mm² 102.37.01-4

Separate circuit for Palladium T2 LED spots

Separate circuit T2 650.00.01

On request

Recessed connecting box
Trimless connecting box
Black or grey textile power cable

Suspension set 2000mm included:

White surface connecting box included
Strain relief integrated
Three suspension wires included
White textile (polyester) power cable included



Photo: Palladium LED interior using 18 Philips Fortimo LED Strips 102mm 6480lm - 46.8W

