

Tunnel 600 T2 Round (+FlatLED T2)


Technical Datasheet

DOXIS
LIGHTING FACTORY



General	
Type	Suspended
Material	Polycarbonate/Steel/Aluminium
Lamp Type	LED Module
Dimmable	Yes
Cooling	Passive
Energy Class	A++
Photobiol. Safety	RG1
Class	class I

IP20 960°C LED




Specifications							
Art. nr.	Lightsource INCLUDED	CCT - CRI	Light output LED/Luminaire (lm)	Efficacy LED/Lumin.* (lm/W)	Power consumpt. LED/Lumin.*	Power supply INCLUDED	SDCM
1265.00.24.830.01	Philips Fortimo LED Line HV + FlatLED T2 spot module	3000K - Ra80	Tunnel: 4832 / 3983 Spot: 1577 / 1388	157 / 112	48.1W / 40.9W	Non dimmable driver	3
1265.00.26.830.01	Philips Fortimo LED Line HV + FlatLED T2 spot module	3000K - Ra80	Tunnel: 4832 / 3983 Spot: 1577 / 1388	157 / 112	48.1W / 40.9W	Touch & DALI dim. driver	3
1265.00.24.840.01	Philips Fortimo LED Line HV + FlatLED T2 spot module	4000K - Ra80	Tunnel: 5200 / 4286 Spot: 1601 / 1409	166 / 118	48.1W / 40.9W	Non dimmable driver	3
1265.00.26.840.01	Philips Fortimo LED Line HV + FlatLED T2 spot module	4000K - Ra80	Tunnel: 5200 / 4286 Spot: 1601 / 1409	166 / 118	48.1W / 40.9W	Touch & DALI dim. driver	3

* Luminaire power consumption/efficacy values of are incl. driver

Lumen Maintenance Philips Fortimo LED Line 3R (Tc=40°C)		
L70B50: >50 000 hrs	L70B20: >50 000 hrs	L70B10: >50 000 hrs
L80B50: >50 000 hrs	L80B20: >50 000 hrs	L80B10: >50 000 hrs
L90B50: >50 000 hrs	L90B20: >50 000 hrs	L90B10: >50 000 hrs

Suspension sets

Suspension set 2000mm (INCLUDED):



- White ceiling box
- Integrated strain relief
- Two steel suspension wires
- 230V White textile supply cable

Suspension set 4000mm (OPTIONAL):

- White 4000mm - 3x0.75mm² 102.23.01-4
- White 4000mm - 5x0.75mm² 102.25.01-4

On request:

- Recessed or trimless connection box
- Black or grey power cable